


# **Black** Recessed Downlight

Art. No.: M5102224

Description: B50DL-15D-4000K











#### **Product description**


Designed to provide optimum high quality downlight, Black incorporates the unique ToD technology in its extreme compact structures to avoid any possible spill light for perfect light control. Multi-functional lighting solutions include fixed, adjustable and wallwasher, together with three dimming methods, all are suitable for new creative freedom in numerous indoor lighting applications.

## **Product features**

- High quality, extreme compact frame made of aluminium ensures excellent heat dissipation
- Rotates through 360°, tilt through 0-25°
- Light aperture: Φ50mm
- Incorporated unique ToD optic system reduce direct glare significantly
- High visual comfort
- High power LED
- Cutout: 54mm
- On-off/DALI/Wireless versions available
- DALI versions occupy 1 address Wireless versions occupy 1 address

## Luminous intensity distribution curve

LED 4W 380lm 4000K



0.26 2828 2.0 0.53 707 3.0 0.79 314 177 4.0 1.06 5.0 1.30 113

H(m) D(m) E(lx)

• Frame - matt white Reflector - specular silver/black/gold

**Technical data** 

AC220V Input Power consumption 5W CRI >90 CCT 4000K Beam angle 15° Chromaticity tolerance <3 SDCM Rated lifetime 50000H (Ta 25°C) Dimming method On-off or DALI/Wireless Dimming range On-off or 0-100% Mechanical adjustment Horizontal: 0-360°; Vertical: 0-25°

Flat A 8/F No.227 Nathan Road Yau Ma Tei Kowloon Hongkong

LITEMATRIX(HK) CO LIMITED

852 30501787 Phone: 852 30506957 Fax:

LiteMatrix reserves the right to make technical and design changes without prior notice.

www.litematrixlighting.com sales@litematrix.net E-mail:

2017.10



# **Black** Recessed Downlight

Art. No.: M5102224

Description: B50DL-15D-4000K

## **Power Supply Info**


| Туре                                   | Dimming  | Art. No.     | Input  | Output | Power   | Address | QTY   |
|--|----------|--------------|--------|--------|---------|---------|-------|
| Constant<br>Current<br>Driver          | On-off   | M9102202.001 | AC220V | 350mA  | 6W      | _       | 1     |
|  | DALI     | M9102202.002 | AC220V | 350mA  | 6W      | 1       | 1     |
|  | Wireless | M9102202.003 | AC220V | 350mA  | 6W      | 1       | 1     |
| Constant<br>Voltage<br>Power<br>Supply | _        | M9102103.001 | AC220V | DC24V  | Max.18W |         | Max.2 |
|  |          | M9102103.003 | AC220V | DC24V  | Max.40W |         | Max.5 |
|  |          | M9102103.005 | AC220V | DC24V  | Max.60W |         | Max.8 |
| DC-DC<br>Driver                        | On-off   | M9102202.005 | DC24V  | 350mA  | _       |         | 1     |
|  | DALI     | M9102202.006 | DC24V  | 350mA  | _       | 1       | 1     |
|  | Wireless | M9102202.007 | DC24V  | 350mA  | _       | 1       | 1     |

M9102201.004 Reflector Specular silver



M9102201.005 Reflector Specular black

## CC(Constant Current Driver) wiring diagram




DO NOT interconnect wires with different colors. Please consider the TOTAL **ADDRESSES** before wiring.




M9102201.010 Reflector Specular gold

### CV(Constant Voltage Power Supply) wiring diagram



DO NOT interconnect wires with different colors. Please consider the TOTAL **ADDRESSES** before wiring.



Mechanical wrench

M9102201.006



M9102201.003 Mechanical hook

Wiring diagrams are examples of typical installations intended to illustrate the number of luminaires that must be connected. These diagrams are not intended to specify all equipment necessary for a given

Please confirm all details with LiteMatrix or suppliers before wiring so as to avoid any unnecessary damage.

LITEMATRIX(HK) CO LIMITED

852 30501787 Phone: 852 30506957 Fax:

changes without prior notice.

2017.10

Flat A 8/F No.227 Nathan Road Yau Ma Tei Kowloon Hongkong www.litematrixlighting.com

sales@litematrix.net E-mail:

LiteMatrix reserves the right to make technical and design