


Black Recessed Downlight

Art. No.: M5102229

Description: B50DL-25D-3000K











Product description

Designed to provide optimum high quality downlight, Black incorporates the unique ToD technology in its extreme compact structures to avoid any possible spill light for perfect light control. Multi-functional lighting solutions include fixed, adjustable and wallwasher, together with three dimming methods, all are suitable for new creative freedom in numerous indoor lighting applications.

Technical data


AC220V Input Power consumption 5W CRI >90 CCT 3000K Beam angle 25° Chromaticity tolerance <3 SDCM Rated lifetime 50000H (Ta 25°C) Dimming method On-off or DALI/Wireless Dimming range On-off or 0-100% Mechanical adjustment Horizontal: 0-360°; Vertical: 0-25°

Product features

- High quality, extreme compact frame made of aluminium ensures excellent heat dissipation
- Rotates through 360°, tilt through 0-25°
- Light aperture: Φ50mm
- Incorporated unique ToD optic system reduce direct glare significantly
- High visual comfort
- High power LED
- Cutout: 54mm
- On-off/DALI/Wireless versions available
- DALI versions occupy 1 address Wireless versions occupy 1 address

Luminous intensity distribution curve

LED 4W 355lm 3000K



E-mail:

H(m) D(m) E(lx) 1.0 0.47 1035 2.0 0.95 259 3.0 1.41 115 4.0 1.90 65 5.0 2.35 41

• Frame - matt white Reflector - specular silver/black/gold

LITEMATRIX(HK) CO LIMITED

Flat A 8/F No.227 Nathan Road Yau Ma Tei Kowloon Hongkong www.litematrixlighting.com

852 30501787 Phone: 852 30506957 Fax:

LiteMatrix reserves the right to make technical and design

sales@litematrix.net

2017.10



Black Recessed Downlight

Art. No.: M5102229

Description: B50DL-25D-3000K

Power Supply Info

Туре	Dimming	Art. No.	Input	Output	Power	Address	QTY
Constant Current Driver	On-off	M9102202.001	AC220V	350mA	6W	_	1
	DALI	M9102202.002	AC220V	350mA	6W	1	1
	Wireless	M9102202.003	AC220V	350mA	6W	1	1
Constant Voltage Power Supply	_	M9102103.001	AC220V	DC24V	Max.18W	_	Max.2
		M9102103.003	AC220V	DC24V	Max.40W	_	Max.5
	_	M9102103.005	AC220V	DC24V	Max.60W	_	Max.8
DC-DC Driver	On-off	M9102202.005	DC24V	350mA	_	_	1
	DALI	M9102202.006	DC24V	350mA		1	1
	Wireless	M9102202.007	DC24V	350mA		1	1

M9102201.004 Reflector Specular silver



M9102201.005 Reflector Specular black



DO NOT interconnect wires with different colors. Please consider the TOTAL **ADDRESSES** before wiring.



M9102201.010 Reflector Specular gold




M9102201.006 Mechanical wrench



M9102201.003 Mechanical hook



CC(Constant Current Driver) wiring diagram



DO NOT interconnect wires with different colors. Please consider the TOTAL **ADDRESSES** before wiring.

Wiring diagrams are examples of typical installations intended to illustrate the number of luminaires that must be connected. These diagrams are not intended to specify all equipment necessary for a given

Please confirm all details with LiteMatrix or suppliers before wiring so as to avoid any unnecessary damage.

LITEMATRIX(HK) CO LIMITED

Flat A 8/F No.227 Nathan Road Yau Ma Tei Kowloon Hongkong

852 30501787 Phone: 852 30506957 Fax:

LiteMatrix reserves the right to make technical and design changes without prior notice.

www.litematrixlighting.com sales@litematrix.net E-mail:

2017.10

2 / 2