

Product description

System X is a perfect integrated lighting system. Thanks to the advanced lighting technology, X series can achieve ultra compact structure and size, with a recessed, surface or suspended installation, that can perfectly integrate into the building and has minimum impact on architecture. Minimalist extruded aluminum profile, available to do flexible continuous connection into any lengths or shapes. Versatile LED lighting Modules are provided for free combination with tool-free installation for all kinds of applications: General Lighting, Accent Lighting, Wallwashing. X not only means inclusiveness, but also the infinity extensions.

Product features

- Compact body made of aluminum
- Easy to be fixed on the track by magnetic force
- Direct light guided by opal diffuser
- The diffuser could be supplied independently as a continuous 30-metre PC roll for easy installation of a continuous LED light line
- On-off/DALI/Wireless dimming available
- DALI versions occupy 1 address
Wireless versions occupy 1 address


- Housing – matt black

Technical data

Input	DC24V
Power consumption	7W
CRI	>90
CCT	3000K
Beam angle	105°
Chromaticity tolerance	<3 SDCM
Rated lifetime	50000H (Ta 25°C)
Dimming method	On-off or DALI/Wireless
Dimming range	On-off or 0-100%

Luminous intensity distribution curve

LED 6.3W 675lm 3000K



H(m)	S(m ²)	Ēm(lx)
3	10x1	61
3	10x2	58
3	10x3	54

QTY: 20


Array: end to end

H: height to calculation area


S: calculating area, length*width

Ēm: average illuminance


Accessories Info




M9103201.001
Diffuser
5m



M9103201.002
Diffuser
10m



M9103201.003
Diffuser
15m



M9103201.004
End cap