

### Product description

System X is a perfect integrated lighting system. Thanks to the advanced lighting technology, X series can achieve ultra compact structure and size, with a recessed, surface or suspended installation, that can perfectly integrate into the building and has minimum impact on architecture. Minimalist extruded aluminum profile, available to do flexible continuous connection into any lengths or shapes. Versatile LED lighting Modules are provided for free combination with tool-free installation for all kinds of applications: General Lighting, Accent Lighting, Wallwashing. X not only means inclusiveness, but also the infinity extensions.

### Product features

- Compact body made of aluminum
- Easy to be fixed on the track by magnetic force
- Direct light guided by opal diffuser
- The diffuser could be supplied independently as a continuous 30-metre PC roll for easy installation of a continuous LED light line
- On-off/DALI/Wireless dimming available
- DALI versions occupy 1 address  
Wireless versions occupy 1 address


- Housing – matt black

### Technical data

Input	DC24V
Power consumption	7W
CRI	>90
CCT	4000K
Beam angle	105°
Chromaticity tolerance	<3 SDCM
Rated lifetime	50000H (Ta 25°C)
Dimming method	On-off or DALI/Wireless
Dimming range	On-off or 0-100%

### Luminous intensity distribution curve

LED 6.3W 720lm 4000K



H(m)	S(m <sup>2</sup> )	Ēm(lx)
3	10x1	65
3	10x2	62
3	10x3	58

QTY: 20


Array: end to end

H: height to calculation area


S: calculating area, length\*width

Ēm: average illuminance


### Accessories Info




**M9103201.001**  
Diffuser  
5m



**M9103201.002**  
Diffuser  
10m



**M9103201.003**  
Diffuser  
15m



**M9103201.004**  
End cap