

Product description

System X is a perfect integrated lighting system. Thanks to the advanced lighting technology, X series can achieve ultra compact structure and size, with a recessed, surface or suspended installation, that can perfectly integrate into the building and has minimum impact on architecture. Minimalist extruded aluminum profile, available to do flexible continuous connection into any lengths or shapes. Versatile LED lighting Modules are provided for free combination with tool-free installation for all kinds of applications: General Lighting, Accent Lighting, Wallwashing. X not only means inclusiveness, but also the infinity extensions.

Product features

- Compact body made of aluminum
- Easy to be fixed on the track by magnetic force
- Unique ToD optic system helps to create high visual comfort
- High power LED
- On-off/DALI/Wireless dimming available
- DALI versions occupy 1 address
Wireless versions occupy 1 address


- Housing – matt white/black
Reflector – specular silver/black

Technical data

Input	DC24V
Power consumption	7W
CRI	>90
CCT	3000K
Beam angle	25°
Chromaticity tolerance	<3 SDCM
Rated lifetime	50000H (Ta 25°C)
Dimming method	On-off or DALI/Wireless
Dimming range	On-off or 0-100%


Luminous intensity distribution curve

LED 5.7W 650lm 3000K




H(m)	D(m)	E(lx)
1.0	0.41	2003
2.0	0.81	501
3.0	1.22	223
4.0	1.63	125
5.0	2.03	80


Accessories Info




M9103301.001
Round Louvre
*3pcs
Specular silver




M9103301.002
Round Louvre
*3pcs
Specular Black



M9103301.003
Quadrate Louvre
*3pcs
Specular silver



M9103301.004
Quadrate Louvre
*3pcs
Specular black



M9103301.009
Mechanical hook