

### Product description

System X is a perfect integrated lighting system. Thanks to the advanced lighting technology, X series can achieve ultra compact structure and size, with a recessed, surface or suspended installation, that can perfectly integrate into the building and has minimum impact on architecture. Minimalist extruded aluminum profile, available to do flexible continuous connection into any lengths or shapes. Versatile LED lighting Modules are provided for free combination with tool-free installation for all kinds of applications: General Lighting, Accent Lighting, Wallwashing. X not only means inclusiveness, but also the infinity extensions.

### Product features

- Compact body made of aluminum
- Easy to be fixed on the track by magnetic force
- Unique ToD optic system helps to create high visual comfort
- High power LED
- On-off/DALI/Wireless dimming available
- DALI versions occupy 1 address  
Wireless versions occupy 1 address


- Housing – matt white/black  
Reflector – specular silver/black

### Technical data

Input	DC24V
Power consumption	7W
CRI	>90
CCT	4000K
Beam angle	25°
Chromaticity tolerance	<3 SDCM
Rated lifetime	50000H (Ta 25°C)
Dimming method	On-off or DALI/Wireless
Dimming range	On-off or 0-100%


### Luminous intensity distribution curve

LED 5.7W 680lm 4000K




H(m)	D(m)	E(lx)
1.0	0.41	2157
2.0	0.81	539
3.0	1.22	240
4.0	1.63	135
5.0	2.03	86


### Accessories Info




**M9103301.001**  
Round Louvre  
\*3pcs  
Specular silver




**M9103301.002**  
Round Louvre  
\*3pcs  
Specular Black



**M9103301.003**  
Quadrate Louvre  
\*3pcs  
Specular silver



**M9103301.004**  
Quadrate Louvre  
\*3pcs  
Specular black



**M9103301.009**  
Mechanical hook