

### Product description

System X is a perfect integrated lighting system. Thanks to the advanced lighting technology, X series can achieve ultra compact structure and size, with a recessed, surface or suspended installation, that can perfectly integrate into the building and has minimum impact on architecture. Minimalist extruded aluminum profile, available to do flexible continuous connection into any lengths or shapes. Versatile LED lighting Modules are provided for free combination with tool-free installation for all kinds of applications: General Lighting, Accent Lighting, Wallwashing. X not only means inclusiveness, but also the infinity extensions.

### Product features

- Compact body made of aluminum
- Rotates through 360° and tilt through 0-90°
- Easy to be fixed on the track by magnetic force
- Deep inside hidden light source and unique ToD optic system helps to create high visual comfort
- High power LED
- On-off/DALI/Wireless/Potentiometer dimming available
- DALI versions occupy 1 address  
Wireless versions occupy 1 address


- Housing – matt black/white  
Reflector – specular silver/black

### Technical data

Input	DC24V
Power consumption	3.5W
CRI	>90
CCT	3000K
Beam angle	18°
Chromaticity tolerance	<3 SDCM
Rated lifetime	50000H (Ta 25°C)
Dimming method	On-off or DALI/Wireless or Potentiometer
Dimming range	On-off or 0-100% or 3%-100%
Mechanical adjustment	Horizontal: 0-360° ; Vertical: 0-90°

### Luminous intensity distribution curve

LED 2.3W 218lm 3000K




H(m)	D(m)	E(lx)
1.0	0.33	1021
2.0	0.66	255
3.0	0.98	113
4.0	1.31	64
5.0	1.64	41


### Accessories Info



**M9102101.001**  
Reflector  
Specular silver



**M9102101.002**  
Reflector  
Specular black



**M9102101.003**  
Mechanical hook



**M9103501.001**  
Cylindrical screen  
(Snoot)